

# ACCU-FRET

ACCU-FRET® FRETWIRE IS MANUFACTURED FROM A NICKEL/SILVER ALLOY, SOMETIMES CALLED "GERMAN SILVER". THE MOST COMMON COMBINATION IS AN 18% NICKEL CONTENT AND THE THREE-QUARTER HARD OR HARDER CONDITION FOR DURABILITY. DUNLOP ACCU-FRET FRETWIRE IS ALSO AVAILABLE IN BRASS AND 18% NICKEL CONTENT IN SOFT CONDITION, AND 12% NICKEL CONTENT IN BOTH HARD AND SOFT CONDITIONS, OFFERING A TREMENDOUS ARRAY OF FRETWIRE FOR LUTHIERS WORLDWIDE.

## ACCU-FRET POUNDS

Fretwire is available coiled, in lengths, or by pound weight. (2 lbs. minimum)

## ACCU-FRET 2 LB. BOX

Contains 2 lbs. of coiled fretwire in a pre-packed box. Please indicate the Fret No. when ordering.

(FRET NO./C2 ACCU-FRET 2 LB. BOX)

## ACCU-FRET TUBES

For the repairman or facility preferring to work with lengths rather than precut material we offer 20 two foot (.609 meter) lengths, straightened.

6T2/(FRET NO.) ACCU-FRET® TUBE


PACKAGED IN A CARDBOARD STORAGE TUBE

## ACCU-FRET SETS

Contains 24 straightened and precut to 2-5/8" (66.67mm) frets. Easy to bend for curved fingerboards.

6S/(FRET NO.) ACCU-FRET® SET

PACKAGED ON A BLISTER PACK CARD



## STANDARD APPLICATIONS

6000	MAXIMUM HEIGHT
6230	FENDER GUITARS
6170	OVERSIZED FRET SLOTS
6130	GIBSON GUITARS ("JUMBO" WIRE)
6290	BANJO
6230	MARTIN GUITARS
6110	BASS
6000, 6100, 6110	MAXIMUM MASS

No.	Material	A		B		C		D		E							
		-	+	-	+	-	+	-	+	-	+						
6000	18% N/S HARD	MM	-0.200	<b>3.250</b>	0.200	-0.150	<b>2.990</b>	0.050	-0.100	<b>0.910</b>	0.050	-0.050	<b>0.530</b>	0.050	-0.075	<b>1.470</b>	0.075
	IN.	-0.008	<b>0.128</b>	0.008	-0.006	<b>0.118</b>	0.002	-0.004	<b>0.036</b>	0.002	-0.002	<b>0.021</b>	0.002	-0.003	<b>0.058</b>	0.003	
6100	18% N/S HARD	MM	-0.200	<b>3.180</b>	0.100	-0.150	<b>2.790</b>	0.050	-0.100	<b>0.810</b>	0.050	-0.050	<b>0.530</b>	0.050	-0.075	<b>1.400</b>	0.075
	IN.	-0.008	<b>0.125</b>	0.004	-0.006	<b>0.110</b>	0.002	-0.004	<b>0.032</b>	0.002	-0.002	<b>0.021</b>	0.002	-0.003	<b>0.055</b>	0.003	
6105	18% N/S HARD	MM	-0.200	<b>2.990</b>	0.200	-0.150	<b>2.290</b>	0.050	-0.100	<b>0.790</b>	0.050	-0.050	<b>0.530</b>	0.050	-0.075	<b>1.400</b>	0.075
	IN.	-0.008	<b>0.118</b>	0.008	-0.006	<b>0.090</b>	0.002	-0.004	<b>0.031</b>	0.002	0.002	<b>0.021</b>	0.002	-0.003	<b>0.055</b>	0.003	
6110	18% N/S HARD	MM	-0.200	<b>2.640</b>	0.100	-0.150	<b>2.920</b>	0.050	-0.100	<b>0.910</b>	0.050	-0.050	<b>0.510</b>	0.050	-0.075	<b>1.270</b>	0.075
	IN.	-0.008	<b>0.104</b>	0.004	-0.006	<b>0.115</b>	0.002	-0.004	<b>0.036</b>	0.002	-0.002	<b>0.020</b>	0.002	-0.003	<b>0.050</b>	0.003	
6120	18% N/S HARD	MM	-0.150	<b>3.000</b>	0.150	-0.050	<b>2.900</b>	0.050	-0.050	<b>0.950</b>	0.030	-0.050	<b>0.600</b>	0.050	-0.030	<b>1.300</b>	0.030
	IN.	-0.006	<b>0.118</b>	0.006	-0.002	<b>0.114</b>	0.002	-0.002	<b>0.037</b>	0.001	-0.002	<b>0.024</b>	0.002	-0.001	<b>0.051</b>	0.001	
6130	18% N/S HARD	MM	-0.203	<b>2.794</b>	0.203	-0.051	<b>2.692</b>	0.051	-0.076	<b>0.914</b>	0.076	-0.051	<b>0.508</b>	0.051	-0.051	<b>0.914</b>	0.051
	IN.	-0.008	<b>0.110</b>	0.008	-0.002	<b>0.106</b>	0.002	-0.003	<b>0.036</b>	0.003	-0.002	<b>0.020</b>	0.002	-0.002	<b>0.036</b>	0.002	
6140	18% N/S HARD	MM	-0.150	<b>2.800</b>	0.150	-0.050	<b>2.700</b>	0.050	-0.050	<b>0.950</b>	0.050	-0.030	<b>0.600</b>	0.030	-0.050	<b>1.000</b>	0.050
	IN.	-0.006	<b>0.110</b>	0.006	-0.002	<b>0.106</b>	0.002	-0.002	<b>0.037</b>	0.002	-0.001	<b>0.024</b>	0.001	-0.002	<b>0.039</b>	0.002	
6150	18% N/S HARD	MM	-0.200	<b>2.743</b>	0.100	-0.150	<b>2.591</b>	0.050	-0.100	<b>0.787</b>	0.050	-0.050	<b>0.510</b>	0.050	-0.075	<b>1.067</b>	0.075
	IN.	-0.008	<b>0.108</b>	0.004	-0.006	<b>0.102</b>	0.002	-0.004	<b>0.031</b>	0.002	-0.002	<b>0.020</b>	0.002	-0.003	<b>0.042</b>	0.003	
6155	18% N/S SOFT	MM	-0.203	<b>2.870</b>	0.203	-0.051	<b>2.616</b>	0.051	-0.076	<b>0.787</b>	0.076	-0.051	<b>0.533</b>	0.051	-0.051	<b>1.168</b>	0.051
	IN.	-0.008	<b>0.113</b>	0.008	-0.002	<b>0.103</b>	0.002	-0.003	<b>0.031</b>	0.003	-0.002	<b>0.021</b>	0.002	-0.002	<b>0.046</b>	0.002	
6160	18% N/S SOFT	MM	-0.150	<b>2.800</b>	0.150	-0.050	<b>2.700</b>	0.050	-0.050	<b>0.950</b>	0.050	-0.040	<b>0.600</b>	0.040	-0.050	<b>1.000</b>	0.050
	IN.	-0.006	<b>0.110</b>	0.006	-0.002	<b>0.106</b>	0.002	-0.002	<b>0.037</b>	0.002	-0.002	<b>0.024</b>	0.002	-0.002	<b>0.039</b>	0.002	
6170	12% N/S HARD	MM	-0.250	<b>3.280</b>	0.250	-0.020	<b>2.500</b>	0.100	-0.250	<b>1.220</b>	0.260	-0.030	<b>0.600</b>	0.020	-0.050	<b>1.100</b>	0.050
	IN.	-0.010	<b>0.129</b>	0.010	-0.001	<b>0.099</b>	0.004	-0.010	<b>0.048</b>	0.010	-0.001	<b>0.024</b>	0.001	-0.002	<b>0.043</b>	0.002	
6180	BRASS	MM	-0.250	<b>2.570</b>	0.250	-0.240	<b>2.720</b>	0.100	-0.250	<b>0.890</b>	0.250	-0.030	<b>0.500</b>	0.180	-0.050	<b>1.100</b>	0.050
	IN.	-0.010	<b>0.101</b>	0.010	-0.009	<b>0.107</b>	0.004	-0.010	<b>0.035</b>	0.010	-0.001	<b>0.020</b>	0.007	-0.002	<b>0.043</b>	0.002	
6190	18% N/S HARD	MM	-0.210	<b>2.390</b>	0.200	-0.050	<b>2.130</b>	0.050	-0.080	<b>0.740</b>	0.070	-0.050	<b>0.510</b>	0.050	-0.050	<b>0.990</b>	0.050
	IN.	-0.008	<b>0.094</b>	0.008	-0.002	<b>0.084</b>	0.002	-0.003	<b>0.029</b>	0.003	0.002	<b>0.020</b>	0.002	-0.002	<b>0.039</b>	0.002	
6200	12% N/S HARD	MM	-0.260	<b>2.540</b>	0.280	-0.020	<b>2.000</b>	0.100	-0.250	<b>1.140</b>	0.260	-0.030	<b>0.600</b>	0.020	-0.100	<b>1.100</b>	0.050
	IN.	-0.010	<b>0.100</b>	0.011	-0.001	<b>0.079</b>	0.004	-0.010	<b>0.045</b>	0.010	-0.001	<b>0.024</b>	0.001	-0.004	<b>0.043</b>	0.002	
6210	12% N/S SOFT	MM	-0.250	<b>2.540</b>	0.250	-0.050	<b>2.000</b>	0.150	-0.270	<b>0.860</b>	0.250	-0.040	<b>0.500</b>	0.040	-0.050	<b>1.100</b>	0.050
	IN.	-0.010	<b>0.100</b>	0.010	-0.002	<b>0.079</b>	0.006	-0.011	<b>0.034</b>	0.010	-0.002	<b>0.020</b>	0.002	-0.002	<b>0.043</b>	0.002	
6220	12% N/S HARD	MM	-0.250	<b>2.400</b>	0.250	-0.020	<b>2.000</b>	0.080	-0.250	<b>0.960</b>	0.250	-0.040	<b>0.500</b>	0.040	-0.050	<b>1.100</b>	0.050
	IN.	-0.010	<b>0.097</b>	0.010	-0.001	<b>0.079</b>	0.003	-0.010	<b>0.038</b>	0.010	-0.002	<b>0.020</b>	0.002	-0.002	<b>0.043</b>	0.002	
6230	18% N/S HARD	MM	-0.260	<b>2.480</b>	0.240	-0.010	<b>1.990</b>	0.100	-0.100	<b>0.900</b>	0.100	-0.060	<b>0.520</b>	0.020	-0.005	<b>1.080</b>	0.070
	IN.	-0.010	<b>0.098</b>	0.009	0.001	<b>0.078</b>	0.004	-0.004	<b>0.035</b>	0.004	-0.002	<b>0.020</b>	0.001	-0.002	<b>0.043</b>	0.003	
6240	18% N/S HARD	MM	-0.203	<b>2.388</b>	0.203	-0.051	<b>2.032</b>	0.051	-0.076	<b>0.787</b>	0.076	-0.051	<b>0.483</b>	0.051	-0.051	<b>0.940</b>	0.051
	IN.	-0.008	<b>0.094</b>	0.008	-0.002	<b>0.080</b>	0.002	-0.003	<b>0.031</b>	0.003	-0.002	<b>0.019</b>	0.002	-0.002	<b>0.037</b>	0.002	
6250	18% N/S HARD	MM	-0.203	<b>2.413</b>	0.203	-0.051	<b>1.905</b>	0.051	-0.076	<b>0.914</b>	0.076	-0.051	<b>0.508</b>	0.051	-0.051	<b>0.762</b>	0.051
	IN.	-0.008	<b>0.095</b>	0.008	-0.002	<b>0.075</b>	0.002	-0.003	<b>0.036</b>	0.003	-0.002	<b>0.020</b>	0.002	-0.002	<b>0.030</b>	0.002	
6260	18% N/S HARD	MM	-0.150	<b>2.800</b>	0.150	-0.100	<b>2.000</b>	0.100	-0.050	<b>0.950</b>	0.050	-0.050	<b>0.600</b>	0.050	-0.030	<b>1.000</b>	0.030
	IN.	-0.006	<b>0.110</b>	0.006	-0.004	<b>0.079</b>	0.004	-0.002	<b>0.037</b>	0.002	-0.002	<b>0.024</b>	0.002	-0.001	<b>0.039</b>	0.001	
6265	18% N/S SOFT	MM	-0.150	<b>2.800</b>	0.150	-0.100	<b>2.000</b>	0.100	-0.050	<b>0.950</b>	0.050	-0.050	<b>0.600</b>	0.050	-0.030	<b>1.000</b>	0.030
	IN.	-0.006	<b>0.110</b>	0.006	-0.004	<b>0.079</b>	0.004	-0.002	<b>0.037</b>	0.002	-0.002	<b>0.024</b>	0.002	-0.001	<b>0.039</b>	0.001	
6270	18% N/S HARD	MM	-0.203	<b>2.540</b>	0.203	-0.051	<b>1.905</b>	0.051	-0.076	<b>0.914</b>	0.076	-0.051	<b>0.508</b>	0.051	-0.051	<b>0.762</b>	0.051
	IN.	-0.008	<b>0.100</b>	0.008	-0.002	<b>0.075</b>	0.002	-0.003	<b>0.036</b>	0.003	-0.002	<b>0.020</b>	0.002	-0.002	<b>0.030</b>	0.002	
6290	18% N/S HARD	MM	-0.203	<b>2.337</b>	0.203	-0.051	<b>1.981</b>	0.051	-0.076	<b>0.787</b>	0.076	-0.051	<b>0.508</b>	0.051	-0.051	<b>1.016</b>	0.051
	IN.	-0.008	<b>0.092</b>	0.008	-0.002	<b>0.078</b>	0.002	-0.003	<b>0.031</b>	0.003	-0.002	<b>0.020</b>	0.002	-0.002	<b>0.040</b>	0.002	
6300	12% N/S HARD	MM	-0.250	<b>1.940</b>	0.250	-0.020	<b>1.600</b>	0.120	-0.250	<b>0.960</b>	0.250	-0.030	<b>0.600</b>	0.020	-0.140	<b>0.640</b>	0.060
	IN.	-0.010	<b>0.076</b>	0.010	-0.001	<b>0.063</b>	0.005	-0.010	<b>0.038</b>	0.010	-0.001	<b>0.024</b>	0.001	-0.006	<b>0.025</b>	0.002	
6310	18% N/S HARD	MM	-0.203	<b>2.311</b>	0.203	-0.051	<b>1.346</b>	0.051	-0.076	<b>0.940</b>	0.076	-0.051	<b>0.559</b>	0.051	-0.051	<b>0.787</b>	0.051
	IN.	-0.008	<b>0.091</b>	0.008	-0.002	<b>0.053</b>	0.002	-0.003	<b>0.037</b>	0.003	-0.002	<b>0.022</b>	0.002	-0.002	<b>0.031</b>	0.002	
6320	18% N/S HARD	MM	-0.203	<b>2.159</b>	0.203	-0.051	<b>1.194</b>	0.051	-0.076	<b>0.717</b>	0.076	-0.051	<b>0.533</b>	0.051	-0.051	<b>0.737</b>	0.051
	IN.	-0.008	<b>0.085</b>	0.008	-0												